

H3061P ☐☐☐☐☐☐☐☐☐☐☐☐☐**230Vac/8A** ☐☐☐☐

□□: H3061P

0000000000000000T+RH000000000000000025
bar01000020040000000000
00



1111

□□□□□□□□□□□□□□□□	250Vac, 8A
□□□□	□□□□□ - □□□
□□□□□□□□	0 to 100%
□□□□□□□□	±2.5%□□□□□5 to 95% at 23°C
□□□□□□□	±0.4°C□ -30 to +100°C□ ±0.4% from reading over +100°C
□□□□□□□	□□□□□□□□
□□□□□□□	-30 to +80°C
□□□□□□□□□	1.5°C □□□□+10°C□□□□□ +25°C□
□□□□□□□□□	2.0°C □□□□+0°C□□□□□ +25°C□
□□□□□□□□□	3.0°C □□□□-10°C□□□□□□ +25°C□
□□□□□□□□□	6.0°C □□□□-20°C□□□□□ +25°C□
□□□□□□□□□□□□	±1.5g/m3□□□□□ T < 25°C□ □□ 0 to 400 g/m3
□□□□□□□□□□□□	±2g/kg□□□□□ T < 35°C□ □□ 0 to 550 g/kg
□□□□□□□□□□□□	±2g/kg□□□□□ T < 35°C□ □□ 0 to 995 g/kg
□□□□□□□□□□□□	±3kJ/kg□□□□□ T < 25°C□ □□: 0 to 995 kJ/kg
□□□□□□□	-30 to +80°C
LCD□□□□□□□□□□□□	□□□□□□+70°C□□□□+70°C□□□□□LCD□□□□
□□□□□□□□□□□□	-30 to +125°C
□□□□□□□□□□□□	0.025mm - □□□□□□□
IP□□□□□	IP65 □□□□□, IP40 □□□□
□□	110 to 240V / 50Hz to 60Hz
□□□□□	230 VAC - □□ 70 mA, 115 VAC - □□ 120 mA
□□□□□□□	G1/2□O□□□
□□□□□□□□□	1m, 2m or 4m □□
□□	136 x 161 x 45 mm (W x H x D), □□□□ 150 mm, □□□□ 18mm
□□	□□ 490g - 1m□□
□□	3□