

# T3113Ex 温湿度露点仪 4-20mA

型号: T3113Ex

ATEX 认证

探头长度 150mm

ATEX 认证



规格

温度范围	-30~135°C
湿度范围	0 to 100%
露点范围	±2.5% RH @ 5 to 95% at 23°C
精度	±0.4°C @ -30~+100°C   ±0.4% RH @ +100°C
分辨率	0.1°C
存储温度范围	±1.5°C @ RH < 30%   -60 to +80°C
存储湿度范围	±1.5g/m <sup>3</sup> @ T < 25°C   0 to 400 g/m <sup>3</sup>
存储露点范围	±2g/kg @ T < 35°C   0 to 550 g/kg
存储精度	±2g/kg @ T < 35°C   0 to 995 g/kg
存储露点精度	±3kJ/kg @ T < 25°C   0 to 995 kJ/kg
工作温度范围	-30 to +60°C
存储温度范围	0~+60°C
LCD 显示温度范围	0~+70°C @ +70°C 时 LCD 熄灭
显示精度	0.1°C
输出 - 模拟	4-20mA, 二线制
输出 - 数字	RS485/PC
探头直径	0.025mm - 0.05mm
IP 等级	IP65 探头 IP40 主机
供电	9-30Vdc
尺寸	88.5 x 250 x 39.5 mm (W x H x D), 探头 150 mm
重量	约 225g
保修	3 年