

T311 RS232

Model: T311



Temperature: ±0.4°C
 Humidity: ±2.5% RH (5 to 95% at 23°C)
 Weight: ±1.5g/m³ (T < 25°C), ±2g/kg (T < 35°C), ±3kJ/kg (T < 25°C)

Specifications

Humidity	0 to 100%
Humidity Accuracy	±2.5% RH (5 to 95% at 23°C)
Temperature	±0.4°C
Temperature Accuracy	±0.4°C
Temperature Range	±1.5°C (T < 25°C) RH > 30% -60 to +80 °C
Weight Accuracy	±1.5g/m³ (T < 25°C) 0 to 400 g/m³
Weight Accuracy	±2g/kg (T < 35°C) 0 to 550 g/kg
Weight Accuracy	±2g/kg (T < 35°C) 0 to 995 g/kg
Weight Accuracy	±3kJ/kg (T < 25°C) 0 to 995 kJ/kg
Operating Temperature	-30 to +80°C
LCD	Monochrome LCD, +70°C
Display	1.5" LCD
Protocol	ModBus RTU, Advantech ADAM
Rate	110 to 115200 Bd
Resolution	0.025mm - 0.01mm
IP Rating	IP65, IP40
Power	9-30Vdc, 6mA
Dimensions	88.5 x 170 x 39.5 mm (W x H x D), 75mm
Weight	230g
Warranty	3 years