

T3319 温湿度传感器 RS232

型号: T3319

传感器长度 1m, 2m, 4m
 1m 传感器长度



规格

湿度	0 to 100%
湿度精度	±2.5% RH @ 5 to 95% at 23°C
温度	±0.4°C @ -30 to +100°C ±0.4% RH @ +100°C
湿度范围	0 to 100%
温度范围	-60 to +80 °C
湿度精度	±1.5% RH @ T < 25°C & RH > 30% ±0.5% RH @ -60 to +80 °C
湿度精度	±1.5g/m ³ @ T < 25°C ±0.5g/m ³ @ 0 to 400 g/m ³
湿度精度	±2g/kg @ T < 35°C ±0.5g/kg @ 0 to 550 g/kg
湿度精度	±2g/kg @ T < 35°C ±0.5g/kg @ 0 to 995 g/kg
湿度精度	±3kJ/kg @ T < 25°C ±0.5kJ/kg @ 0 to 995 kJ/kg
湿度范围	-30 to +80°C
LCD 显示屏	背光 +70°C 背光 +70°C LCD 显示屏
通信协议	ModBus RTU / Advantech ADAM
波特率	110 to 115200 Bd
传感器长度	0.025mm - 4m
IP 等级	IP65 / IP40
供电	9-30Vdc, 最大 6mA
传感器长度	1m, 2m, 4m
尺寸	88.5 x 114 x 39.5 mm (W x H x D), 孔径 88 mm, 孔径 18mm
重量	约 290g - 1m 传感器
包装	3 个