

T3411 RS485

Model: T3411

Features:
 - High accuracy
 - RS485 interface
 - Wide range of measurements



Specifications

Humidity	0 to 100%
Humidity Accuracy	±2.5% RH (5 to 95% at 23°C)
Temperature	±0.4°C
Temperature Accuracy	±0.1°C
Temperature Range	±1.5°C (T < 25°C, RH > 30%) -60 to +80°C
Humidity Range	±1.5g/m ³ (T < 25°C) 0 to 400 g/m ³
Humidity Accuracy	±2g/kg (T < 35°C) 0 to 550 g/kg
Humidity Accuracy	±2g/kg (T < 35°C) 0 to 995 g/kg
Humidity Accuracy	±3kJ/kg (T < 25°C) 0 to 995 kJ/kg
Temperature Range	-30 to +80°C
LCD Display	Monochrome +70°C, Monochrome +70°C, LCD
Communication	ModBus
Protocol	ModBus RTU, Advantech ADAM
Rate	110 to 115200 Bd
Resolution	0.025mm - 0.001mm
IP Rating	IP65, IP40
Power	9-30Vdc, 0.5W
Dimensions	88.5 x 170 x 39.5 mm (W x H x D), 75mm
Weight	150g
Warranty	3 years