

T3419 RS485

Model: T3419

Available cable lengths: 1m, 2m, 4m
 Cable length: 1m



Table

Humidity	0 to 100%
Humidity Accuracy	±2.5% RH (5 to 95% at 23°C)
Temperature	±0.4°C (-30 to +100°C) / ±0.4% RH (+100°C)
Temperature Accuracy	±0.4% RH (+100°C)
Temperature Range	-60 to +80 °C
Temperature Accuracy (RH > 30%)	±1.5°C (T < 25°C) / ±0.4% RH (-60 to +80 °C)
Humidity Accuracy (T < 25°C)	±1.5g/m ³ (T < 25°C) / ±0.4% RH (0 to 400 g/m ³)
Humidity Accuracy (T < 35°C)	±2g/kg (T < 35°C) / ±0.4% RH (0 to 550 g/kg)
Humidity Accuracy (T < 35°C)	±2g/kg (T < 35°C) / ±0.4% RH (0 to 995 g/kg)
Humidity Accuracy (T < 25°C)	±3kJ/kg (T < 25°C) / ±0.4% RH (0 to 995 kJ/kg)
Temperature Range	-30 to +80°C
LCD Display	Backlit LCD (+70°C) / LCD (+70°C)
Communication	ModBus RTU / Advantech ADAM
Communication Rate	110 to 115200 Bd
Cable Length	0.025mm - 1m
IP Rating	IP65 / IP40
Power	9-30Vdc, 0.5W
Cable Length	1m, 2m, 4m
Dimensions	88.5 x 114 x 39.5 mm (W x H x D), 88 mm, 18mm
Weight	210g - 1m
Quantity	3