

H6540 CO2

□□: T6540

CO2 emissions t-line
CO2 emissions



A multiple point CO₂ and temperature adjustment Δ CO₂ Δ Temp
 Δ CO₂ Δ Temp; Δ CO₂ Δ Temp.
 NDIR Δ CO₂ Δ Temp Δ CO₂ Δ Temp

[illegible]

Easy wireless communication using **Web Sensor** and optional **Wireless TP-LINK router**.



□□□□

CO2濃度	0 to 2000ppm
CO2濃度	±(50ppm +2%) at 25°C and 1013hPa
CO2濃度	0 to 10000ppm ±(100ppm +5%) at 25°C and 1013hPa
湿度	0 to 100%
湿度	±2.5% RH 5 to 95% at 23°C
温度	±0.6°C
温度	0.1°C, 0.1%RH, 1ppm
温度	2s
CO2濃度	15s
温度	温度补偿
湿度	湿度补偿
温度	±1.5°C 温度T<25°C RH>30% -60 to +80 °C
湿度	湿度补偿
温度	-30 to +60°C
IP	IP30
LAN	RJ-45 10Base-T 100Base-TX
通信	WWW, ModbusTCP, SNMPv1, SOAP
通信	E-mail (SMTP) SNMP Trap Syslog
通信	T-Sensor, WWW
电压	9-30Vdc, 1W
尺寸	尺寸, 5.5 x 2.1mm
重量	88.5 x 147.5 x 39.5mm (W x H x D), 75 mm

□□	□□160g
□□	3□