

□□□□□□□□□□**GSM**□□□□□□□□□□**IoT**□□□□□□□□□□

□□: U0843M



GSM
MSJSON

JSON COMET LED LCD

☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ USB-C ☐ ☐ ☐ ☐ ☐

GSM 17025 EN ISO/IEC

1111

000000 - 0000PT1000	
0000	-200 ° +260 °C
0000	±0.2°C00+100 ° +260°C0000000 ±0,2 %0
000	0.1 °C 00000000 V 00000000+30 V DC
000000000t90 (000020°C00001m/s)	00000000
00000	
0000000	00000000 < 0,4 V(*); 00000000 > 2 V; 000000000 V 00000000+30 V DC
00000000	0“00”000000000 < 10 kOhm ; 0“00”000000000 > 300 kOhm ; 0“00”0000000003 V; 0000000000000000001s
0000000	
0000	-20 ° +60 °C
00	20000000020000000
000000	00000000000500,00000000000000000350,00000
00000000000	00100240000
00000000	100100010000
0000000	000 - 000000000000000 - 0000000000000000
0000	0000000000000000
00	00 SONY Lilon 5200mAh
0000	IP20
00	61 x 93 x 53 mm, 000 120 x 93 x 53 mm
0000000000	0270 g
00	30