

H3060

Model: H3060

The H3060 is a portable, rugged, and accurate environmental chamber. It is designed for use in a wide range of applications, from industrial to scientific. The H3060 is available in two versions: a standard version and a high-precision version.



Table

Power supply	250Vac, 8A
Temperature range	0 to 100 °C
Humidity range	0 to 100%
Temperature accuracy	±2.5% RH at 23 °C
Humidity accuracy	±0.4 °C
Temperature stability	±0.01 °C
Humidity stability	±1.5 °C at T < 25 °C, RH > 30% at -60 to +80 °C
Temperature resolution	±1.5g/m ³ at T < 25 °C, RH > 30% at 0 to 400 g/m ³
Humidity resolution	±2g/kg at T < 35 °C, RH > 30% at 0 to 550 g/kg
Temperature resolution	±2g/kg at T < 35 °C, RH > 30% at 0 to 995 g/kg
Humidity resolution	±3kJ/kg at T < 25 °C, RH > 30% at 0 to 995 kJ/kg
Temperature range	-30 to +80 °C
LCD display	0.025mm - 0.025mm LCD display
Temperature range	0.025mm - 0.025mm
Humidity range	0.025mm - 0.025mm
IP rating	IP65, IP40, IP40
Power	110 to 240V / 50Hz to 60Hz
Power	230 VAC - 70 mA, 115 VAC - 120 mA
Power	136 x 214 x 45 mm (W x H x D), 75mm
Power	390g
Power	3