

M1220 2-Channel MiniDIN 2-Channel

Model: M1220



2-Channel MiniDIN 2-Channel
 2-Channel MiniDIN 2-Channel
 2-Channel MiniDIN 2-Channel
 2-Channel MiniDIN 2-Channel
 2-Channel MiniDIN 2-Channel
 2-Channel MiniDIN 2-Channel
 2-Channel MiniDIN 2-Channel

Table

| | |
|--------------------|--|
| Temperature | -10 to +60°C |
| Humidity | 5% to 85%RH, non-condensing |
| Resolution | 0.1°C |
| Accuracy | ±1s ±24mm |
| Response Time | Fast, 100ms |
| Power | Rechargeable battery |
| Capacity (approx.) | 1 000 000 samples (internal), 600 000 samples (external) |
| IP Rating | IP20 |
| Connectivity | Ethernet, USB, RS232 |
| Protocols | WWW, SNMPv1, XML, DATALINK |
| Alerts | E-Mail |
| Display | Comet Vision, WWW |
| Power Supply | AC 230Vac/5Vdc (rechargeable) |
| Battery | NiMH 3x1.2V AA (rechargeable) or 3x1.5V AA (standard) |
| Dimensions | 5.5 x 2.1mm |
| Weight | 178 x 95 x 37mm (W x H x D), 100g |