

P8541 -

Model: P8541



OMET p-line

Easy wireless communication using Web Sensor.



Table

DSTR162/C, DSTGL40/C, DSTG8/C	$\pm 0.5^{\circ}\text{C}$ from -10 to $+80^{\circ}\text{C}$, else $\pm 2^{\circ}\text{C}$
DSRH01, DSRH02, DSRH05	$\pm 3.5\%$ RH (10% - 90% RH) at 25°C , $\pm 2^{\circ}\text{C}$
DSTR162/C, DSTGL40/C	-30 to $+80^{\circ}\text{C}$
DSTG8/C	-50 to $+100^{\circ}\text{C}$
DSRH01, DSRH02, DSRH05	0 to 100%RH (not condensing)
DSRH01, DSRH02, DSRH05	0 to $+50^{\circ}\text{C}$
Resolution	0.1°C , 0.1% RH
Response time	2s
Power supply	5Vdc, 1W
Power supply	-30 to $+80^{\circ}\text{C}$
IP	IP30
LAN	RJ-45 10Base-T 100Base-TX
Protocols	WWW, ModbusTCP, SNMPv1, SOAP
Protocols	E-mail (SMTP) SNMP Trap Syslog
Accessories	T-Sensor, Telnet, keyboard
Power	5Vdc, 1W
Dimensions	88 x 74 x 39.5 mm (W x H x D)
Weight	135g
Life	3 years