

T3110Ex

Model: T3110Ex

ATEX certified for use in explosive atmospheres
 Complies with the requirements of the ATEX Directive 94/9/EC

ATEX Zone.



Features

Humidity range	0 to 100%
Humidity accuracy	±2.5% RH (5 to 95% at 23°C)
Temperature range	±0.4°C
Temperature accuracy	±0.1°C
Operating temperature	±1.5°C (T < 25°C) RH > 30% -60 to +80 °C
Operating humidity	±1.5g/m³ (T < 25°C) 0 to 400 g/m³
Operating pressure	±2g/kg (T < 35°C) 0 to 550 g/kg
Operating altitude	±2g/kg (T < 35°C) 0 to 995 g/kg
Operating energy	±3kJ/kg (T < 25°C) 0 to 995 kJ/kg
Operating voltage	-30 to +60°C
Operating pressure	±60°C
LCD display	±70°C (T < 70°C) LCD display
Operating mode	Normal
Output - 4-20mA	4-20mA, 0.1mA
Operating mode	Normal PC mode
Operating pressure	0.025mm - 0.05mm
IP rating	IP65 (T < 40°C)
Power	9-30Vdc
Size	88.5 x 170 x 39.5 mm (W x H x D), 75 mm
Weight	150g
Life	3 years