

T3419 RS485

Model: T3419

Available cable lengths: 1m, 2m, 4m
 Available cable lengths: 1m



Table

Humidity	0 to 100%
Humidity Accuracy	±2.5% RH @ 5 to 95% at 23°C
Temperature	±0.4°C @ -30 to +100°C
Temperature Accuracy	±0.4% @ +100°C
Temperature Range	-60 to +80 °C
Temperature Accuracy (RH > 30%)	±1.5°C @ T < 25°C
Temperature Accuracy (RH > 30%)	-60 to +80 °C
Humidity Accuracy (T < 25°C)	±1.5g/m ³
Humidity Accuracy (T < 35°C)	±2g/kg
Humidity Accuracy (T < 35°C)	±2g/kg
Humidity Accuracy (T < 25°C)	±3kJ/kg
Temperature Range	-30 to +80°C
LCD Display	Two-line LCD @ +70°C
Communication	ModBus RTU
Communication	Advantech ADAM
Communication	110 to 115200 Bd
Communication	0.025mm - 0.1mm
IP Rating	IP65
Power	9-30Vdc, 0.5W
Cable Length	1m, 2m, 4m
Dimensions	88.5 x 114 x 39.5 mm (W x H x D), 88 mm, 18mm
Weight	210g - 1m
Quantity	3