

T7410 - RS485

Model: T7410

Features: RS485, LCD



Table

Humidity	0 to 100%
Humidity Accuracy	±2.5% RH @ 5 to 95% at 23°C
Temperature Accuracy	±0.4°C
Temperature Range	-60 to +80 °C
Temperature Accuracy (RH > 30%)	±1.5°C @ T < 25°C
Humidity Accuracy (T < 25°C)	±1.5g/m ³
Humidity Accuracy (T < 35°C)	±2g/kg
Humidity Accuracy (T < 35°C)	±2g/kg
Humidity Accuracy (T < 25°C)	±3kJ/kg
Pressure Range	600 to 1100hPa
Pressure Accuracy	±(1,3hPa+0.06% of reading) at 23°C from 800 to 1100hPa
Pressure Units	hPa, kPa, mbar, mmHg, inHg, inH ₂ O, PSI, oz/in ²
Temperature Range	-30 to +80°C
LCD Display	Monochrome LCD
Communication	ModBus RTU
Communication	Advantech ADAM
Communication	110 to 115200 Bd
Dimensions	0.025mm - 0.001"
IP Rating	IP54, IP40
Power	9-30Vdc, 0.5W
Dimensions	88.5 x 170 x 39.5 mm (W x H x D), 75 mm
Weight	150g
Warranty	3