

# IoT 3 0-20 mA 1 GSM

U6841M



GSM 3 1 GPRS SMS JSON [COMET Cloud](#)

JSON COMET LED LCD

USB-C

EN ISO/IEC 17025

Table

|                       |                                  |
|-----------------------|----------------------------------|
| Supply Voltage        | 0 - 20 mA DC                     |
| Supply Current        | 1 μA                             |
| Accuracy              | ±20 μA                           |
| Resolution            | 100 Ω                            |
| Output Current        | 0 mA (typical)                   |
| Output Voltage        | 40 mA                            |
| Operating Voltage     |                                  |
| Operating Temperature | 0,8 V(*); > 2 V; 0 V; +30 V DC   |
| Input Impedance       | 10 kOhm; > 2 MOhm; 3 V; 1s       |
| Storage Temperature   |                                  |
| Operating Temperature | -20 - +60 °C                     |
| Humidity              | 3x, 1x                           |
| Life Cycle            | 500,000 350,000                  |
| Dimensions            | 1x24                             |
| Weight                | 10x10x1                          |
| Material              | - -                              |
| Power Source          |                                  |
| Battery               | SONY Lilon 5200 mAh              |
| Protection Class      | IP20                             |
| Dimensions (mm)       | 61 x 93 x 53 mm 120 x 93 x 53 mm |
| Weight (g)            | 270 g                            |
| Quantity              | 3                                |